

MAXIMATOR®

Maximum Pressure.



High Pressure Technology • Testing Equipment
Hydraulics • Pneumatics

Technical Data Sheet

Air Actuated H2-Valve 15V9M071-H2-8MNC



Technical Data

Operating temperature:	-40°C / +85°C
Drive pressure:	73 psi-145 psi (5 bar-10 bar)
Operating pressure:	15200 psi (1050 bar)
Net weight:	16,8 kg

Materials:

Valve body:	1.4404
Valve stem:	1.4980
Seal:	UHMWPE

Dimensions:

Height:	291 mm
Width:	220 mm x 220 mm
Orifice:	7,9 mm

Actuator:	8MNC
------------------	------

Catalog Part Number

Pressure	Component Type	Connection Size	Type	Stem Type	Body pattern	Media	Configuration
15 = 15200 psi (1050 bar)	V = Valve	9 = 9/16"	M = Medium pressure	07 = Vee stem	1 = Two-way straight	H2	8MNC = Air drive normally closed
					2 = Two-way angle		



The valves are marked with an EX sign and are in conformity to Group II Category 2G/2D Explosion group IIC constructive safety.

Please consult factory for more information. All technical and dimensional information subject to change. All General Terms and Conditions of sale, including limitations of our liability, apply to all products and services sold.

MAXIMATOR®

Maximum Pressure.



High Pressure Technology • Testing Equipment
Hydraulics • Pneumatics

15V9M071-H2-8MNC:

