



MAXIMATOR®

maximum pressure

Technical Data Sheet

GPD120-2

» Oil and Water Service



GPD120-2
double acting, double air drive head

Technical Data:

Air drive pressure:	1 - 10 bar / 14.5 - 145 psi
Calculated working pressure:	1800 bar / 26100 psi
Pressure ratio:	1:258
Displacement volume/double stroke	121 cm ³ / 7.4 cu.inch

Connections:

Inlet:	BSP 3/4"
Outlet:	9M (9/16")
Air drive:	BSP 3/4"
Maximum operating temperature:	60°C
Net weight:	78 kg

Pressure and flow performances, please see enclosed graph.



Pumps of the GPD Series that are marked with an EX sign and are supplied with a declaration of conformity as defined in 94/9/EC may be used in areas subject to explosion hazards. They are in conformity to Group II Category 2G Explosion group IIC constructive safety.

Wetted materials of construction:	Seal package:	GPD 120-2: UHMWPE, FKM
-----------------------------------	---------------	------------------------

Pump Body:	1.4542
------------	--------

Piston:	1.4542
---------	--------

Fittings:	1.4542
-----------	--------

Approximate Dimensions:

A:	1019 mm
----	---------

B:	293 mm
----	--------

C:	343 mm
----	--------

Available Options:

Inlet and Outlet piping to one common inlet and one common outlet port
--

Available Accessories:

Air control units with filter pressure regulator, control pressure gauge and shut off valve:	GPD120-2 with C3
--	------------------

To protect the pump against excessive outlet pressures or to limit the outlet pressure, a safety valve can be fitted to the air control unit in the air drive line.	GPD120-2 with C3/SV-air (The required outlet pressure has to be indicated.)
---	---

Please consult factory for more information. All technical and dimensional information subject to change. All General Terms and Conditions of sale, including limitations of our liability, apply to all products and services sold.

MAXIMATOR®

maximum pressure

